	XX	AAAAA AAAAA AA AA AA AA AA AA A	MM MM MM MM MM MM MMM MMM MM MM MM MM MM MM	PPPPPPPPPPPPPPPPPPPPPPPPPPPPPPPPPPPPPP	LL		\$
--	----	---	--	--	--	--	--

LPF

	AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA	88888888 88 88 88 88 88 88 88 88 88 88 88 88 888888	000000 000000 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00	\$		AAAAA AA AA AA AA AA AA AA AA AA AA AA AA AAAAAAAA	
FFFFFFFFFFFFFFFFFFFFFFFFFFFFFFFFFFFFFF	000000 000000 00	RRRRRRRR RRRRRRRR RR RR RR RR RR RR RRRRRR					

C

ř 5

5

_

C C 6

.

C C C 7

C C C C 8

1 🛊

1 *

LB

8(

```
!File: LABIOSTAT.FOR 
! Version 'V04-000'
```

COPYRIGHT (c) 1978, 1980, 1982, 1984 BY DIGITAL EQUIPMENT CORPORATION, MAYNARD, MASSACHUSETTS. ALL RIGHTS RESERVED.

THIS SOFTWARE IS FURNISHED UNDER A LICENSE AND MAY BE USED AND COPIED ONLY IN ACCORDANCE WITH THE TERMS OF SUCH LICENSE AND WITH THE INCLUSION OF THE ABOVE COPYRIGHT NOTICE. THIS SOFTWARE OR ANY OTHER COPIES THEREOF MAY NOT BE PROVIDED OR OTHERWISE MADE AVAILABLE TO ANY OTHER PERSON. NO TITLE TO AND OWNERSHIP OF THE SOFTWARE IS HEREBY TRANSFERRED.

THE INFORMATION IN THIS SOFTWARE IS SUBJECT TO CHANGE WITHOUT NOTICE AND SHOULD NOT BE CONSTRUED AS A COMMITMENT BY DIGITAL EQUIPMENT CORPORATION.

DIGITAL ASSUMES NO RESPONSIBILITY FOR THE USE OR RELIABILITY OF ITS SOFTWARE ON EQUIPMENT WHICH IS NOT SUPPLIED BY DIGITAL.

Program LABIO_STATUS
This is a utility routine for the LABIO system. It displays the status of all 16 channels of the A/D. It assumes that the terminal is a VT52 or an equivalent, e.g VT100 in VT52 mode. The display is update once every 1-9 seconds. Default is one second. There are 5 commands associated with the program

C - display status of 16 channels P - display status by process PID H - display help frame (timeouts after 1 min.) E - Exit to VMS DCL Digit(1-9) Change cycle time.

The key pad can also be used to enter commands. The special function Keys on the VT52 or VT100 correspond to the first 4 commands (3 on VT52).

! Typing ANY key will cause a display refresh.

Include 'LABCHNDEF.FOR'

Character*10 STATUS(4)
Character*8 XTIME
Character*9 XDATE
Parameter COMMAND MAX = 4
Character*1 COMMAND,COMMAND_TABLE(COMMAND_MAX,2),ESCAPE,TERMINATOR
Character*03 COMMAND_DEV

External SS\$ NOTRAN,SS\$ NORMAL,SS\$ PARTESCAPE External IO\$M_CVTLOW,IO\$M_NOECHO,IO\$M_TIMED,IO\$_READVBLK,IO\$M_PURGE

PURGE = 0

```
Equivalence (ESCAPE, HOME), (CHAR_COUNT, 10_STATUS(2))
  VT52 control ESCAPE Sequences
        Data HOME, ERASE SCREEN, ERASE LINE
1 /'33'0, 'H', '33'0, 'J', '33'0, 'K'/
  VI100 control ESCAPE sequences
 This ESC seq places a VT100 in VT52 mode
        Data VT52_MODE/'33'0,'[','?','2','L','33'0,']'/
        Data STATUS/'Unknown ','Inactive',' Active ',' /
Data COMMAND_TABLE/'C','P','E','H','P','Q','S','R'/
Data DISPLAY_FLAG,ERASE_FLAG /1,.TRUE./
        Data DEF_TIME_OUT /1/
 Map to the GLOBAL DATA section created by the I/O program
        Call LABIO_INIT(0)
 Place VT100's in VT52 mode
        Type 500, VT52_MODE
 Initialize Command input channel
 We will read the command via a QIOW with a 1 sec timeout
 Commands are single character, to simplify matters we will
 read with no echo and convert lower to upper case.
        Call SYS$ASSIGN( 'TT', COMMAND_CHAN,,,)
QIO_READ = %Loc(IO$M_NOECHO) + %Loc(IO$M_CVTLOW) + %Loc(IO$M_TIMED)
        1 + XLoc(IOS_READVBLR)
        TT_PURGE = %Coc(IO$M_PURGE)
        GoTo 25
                                   ! Display Something
 Get a command from the user, but only wait a short time (TIME_OUT)
 so we can update the screen. The input buffer is purged if a command
 was decode on the last read. (Prevents unnecessary erase loops)
20
        DISPLAY_FLAG = OLD_DISPLAY !Default is last display
                                      !Default time out
        TIME_OUT = DEF_TIME_OUT
21
        TABLE_INDEX = 1
                                      !Assume no escape sequence
22
        Call SYS$QIOW(, %Val(COMMAND_CHAN), %Val(QIO_READ+PURGE),
        1 IO_STATUS,,,%Ref(COMMAND),%Val(1),%Val(TIME_OUT),,,,)
```

```
0000
C
```

C

LP

```
! If escape seq., set command table pointer to second table and ! get character following escape.

TERMINATOR = Char( IO_STATUS(3) )

If( TERMINATOR .ne. ESCAPE ) Go To 23
          TABLE_INDEX = 2
Go To 22
                                !Get char following escape
23 If (CHAR_COUNT .ne. 0) Then ! Check for char 1-9
                                                      ! Char count not 0
             If( COMMAND .ge. '0' .and. COMMAND .le. '9' ) Then
   DEF_TIME_OUT = Ichar ( COMMAND ) - Ichar( '0' )
! Not 1-9 try a command.
             Else
                ERASE_FLAG = .true.
Do 24 I = 1, COMMAND_MAX
                                                      ! Screen erase
                if( COMMAND .eq. COMMAND_TABLE(I,TABLE_INDEX)) DISPLAY_FLAG = I
24
                Continue
             End If
             PURGE = TT_PURGE
                                                      !Purge the input buffer next time
          End If
  Get date and time, then dispatch to display routine
25
          Call DATE (XDATE)
          Call TIME (XTIME)
          Go to (50,60,99,40) DISPLAY_FLAG
 Refresh the screen (Erase and Redisplay)
30
          DISPLAY FLAG = OLD_DISPLAY ERASE_FEAG = .true.
Go To 25
                                                      !Redisplay last display
! Display the HELP frame, set the temporary time-out to 1 minute
40
          Type 600, HOME, ERASE_SCREEN TIME_OUT = 60
                                                      !Display the help frame
                                                      !Give the user 1 minute to read it
          DISPLAY FLAG = OLD_DISPLAY ERASE_FLAG = .true.
                                                      !When it times out, default old
          Go To 21
  Generate the Status Line for each A/D channel
50
          If ( ERASE_FLAG ) Type 300, HOME, ERASE_SCREEN
Type 100, HOME, XTIME, XDATE
CHANNEL_COUNT = 0
          Do 51 CHANNEL = 1.MAX AD CHANNEL If ( AD_BLOCK(2, CHANNEL) .ne. 0 ) Then
                                                                  !If allocated, display info
          Type 200, CHANNEL, STATUS (AD_BLOCK (1, CHANNEL)+1), 1 (AD_BLOCK (J, CHANNEL), J = 2,6)
             CHARNEL_COUNT = CHANNEL_COUNT + 1
                                                               !If not allocated, say so
             Type 900, CHANNEL, '<Unused>', ERASE_LINE
          End 1f
51
          Continue
```

LP

Ç

C

C

C

21

C

CCC

10 10

10

C

C

C

10

C

```
PID_COUNT = 0
Do 52 PID_INDEX = 1, MAX_PID
PID = CONNECT_BLOCK(PID_INDEX,1)
If ( PID .ne. 0 ) PID_COUNT = PID_COUNT + 1
52
            Continue
           Type 400, ERASE_LINE, PID_COUNT, CHANNEL_COUNT OLD_DISPLAY = DISPLAY_FLAG
           ERASE_FLAG = .false.
            Go to 20
  Status display via process (PID)
           If ( ERASE_FLAG ) Type 300, HOME,ERASE_SCREEN
Type 100, HOME,XTIME,XDATE
PID_COUNT = 0 ! Number of continuous process.
60
                                                             Number of connected processess
           CHARNEL COUNT = 0
Do 61 PID_INDEX = 1, MAX_PID
                                                           ! Number of allocated channels
           PID = CONNECT_BLOCK(PID_INDEX,1)

If ( PID .ne. 0 ) Then

PID_COUNT = PID_COUNT + 1
           OLD COUNT = CHANNEL COUNT

DO 62 CHANNEL = 1, MAX AD CHANNEL

If (AD BLOCK (2, CHANNEL) Then ! If right PID, display info

Type 200, CHANNEL, STATUS (AD BLOCK (1, CHANNEL) + 1),

1 (AD BLOCK (J, CHANNEL), J = 2,6)

CHANNEL COUNT TO CHANNEL (1)
                 CHANNEL_COUNT = CHANNEL_COUNT + 1
               End If
62
              Continue
           If (OLD_COUNT .eq. CHANNEL_COUNT ) Type 800, '<None>',PID,ERASE_LINE
           End If
61
           Continue
           Type 400.ERASE_LINE.PID_COUNT.CHANNEL_COUNT.ERASE_SCREEN OLD_DISPLAY = DISPLAY_FEAG
           ERASE_FLAG = .false.
Go to 20
Exit
99
           Call Exit
  Formai Statments
           Format(1X,2A1,'
1' Channel Status
100
                                                  Lab IO Status as of '.A.' '.A//
                                                             Tics/Sample Buffer Size
                                                  PID
                       Buffers '/)
200
           format(15,5x,A8,Z10,4112)
300
            Format(' ',4A1)
            400
```

```
500
           Format(' '7A1)
          format(' '4A1/
1' The following commands are available: '//
1' VT100 VT52 any'/
600
                                                     Channel Display'/
Process Display'/
Help Display'/
Exit'//
                      PF1
                                red
                      PF2
PF3
                                blue
                                grey
n/a
                      PF4
           1' To change display time, type a digit 0-9 for the desired time'//) Format(A)
700
800
           Format(' ',A6,11X,Z10,2A1)
900
           Format(15,5x,A8,2A1)
End ![End of file]
```

18

30

c c 12

CCC

10

CCC

10

CCC

10

CCC

10

CCC

10

0158 AH-BT13A-SE VAX/VMS V4.0

DIGITAL EQUIPMENT CORPORATION CONFIDENTIAL AND PROPRIETARY

